



Intertape® Brand Industrial Tapes offer the best performance, quality and value for light utility to high performance applications. Providing the most comprehensive and robust product line in the industry, Intertape Polymer Group™ has the ideal solution to your most demanding situations.

### **Table of Contents:**

Masking Tape	············	
Flatback Tape		
Filament/MOPP Tape		
Cloth/Duct Tape		1
Double-Coated Tape		1
Specialty Products		1

### **IPG Product Offering:**

#### As a leading manufacturer of industrial tapes in North America, Intertape Polymer

**Group™** (IPG), is proud of our extensive industrial product offering. No other supplier can make the commitment we have to our market and customers. Our philosophy to develop exciting new products and markets and bundle them with our strategic suppliers, premier products and dedicated distributors, makes IPG the supplier of choice.

Hot-Melt Carton-Sealing Tape
Acrylic Carton-Sealing Tape
Natural Rubber Carton-Sealing Tape
Water Activated (WAT) Carton-Sealing Tape
Cloth/Duct HVAC Tape
Masking Tape

Flatback Tape
Electronic Tape
Electrical Tape
Filament Tape
Glass/Cloth Tape
Packaging Equipment

# **Masking Tape**

Intertape® Brand Masking Tape is designed for superior performance for a variety of applications. Paint masking, holding, light-duty work, splicing, bundling or packaging, Intertape® Brand has the right masking tape for the job.



		Thickness (mils)	Elongation %	Adhesion (oz/in)	Tensile (lb/in)	Adhesive Type
<b>Utility Gra</b>	ade					
PG500	Intended for non-critical room temperature applications such as hanging paper, poly and poster board. A great stationary masking tape.	4.8	9.0	43	22	Solvent- less SIS
PG511	A thin masking tape which provides clean paint lines. Also removes cleanly and works in many temperatures. Ideal for non-critical painting applications.	5.0	7.0	26	20	Solvent NR
General G	Grade					
PG415	A robust utility grade masking product for non-critical securing and bundling applications. A very conformable backing with an aggressive adhesive.	5.1	8.0	35	15	Solvent NR/SIS
515	A tried and proven industry leader. The high adhesion of this solvent cast natural and synthetic rubber blend make 515 great for masking, bundling and holding.	5.5	7.0	48	23	Solvent NR/SIS
PG505	Designed for the painting contractors, PG505 is an industry staple. With a high elongation PG505 can bend and confirm to most painting designs and applications.	6.0	10.0	33	20	Solvent NR
Medium (	Grade					
519	When performance begins to be critical, 519 is an all around performer. The solvent cast natural and synthetic rubber platform allows 519 to adhere to many surfaces where other maskings cannot.	6.0	7.0	43	23	Solvent NR/SIS
PG501	A medium grade masking tape with a full natural rubber-based adhesive platform. Both the adhesive platform and backing are resistant to moisture allowing PG501 to outperform other masking tapes where humidity levels are higher such as tropical climates.	5.5	9.0	32	26	Solvent NR
Premium	Grade					
PG5	Recognized as the premium painter's tape in the industry, PG5 is demanded world wide. The smooth textured backing makes PG5 easy to apply while providing clean and crisp paint lines.	6.3	10.0	33	25	Solvent NR
PG29	IPG's heaviest Premium Grade Tape makes masking interiors easy. Lower adhesion makes removal easy while not damaging delicate surfaces.	6.8	10.0	25	25	Solvent SIS
PG56	When performance counts PG56 leads the way. Temperature resistant to 225°F/107°C allows PG56 to be used in any medium temperature automotive painting application.	6.4	9.0	33	23	Solvent NR
Temperat	cure Resistant					
527	An easy to apply, clean removing masking used for spray painting primarily in the automotive industry, but also used in construction and printed circuit board manufacturing. Temperature resistant to 265° F.	6.1	7.0	41	23	Solvent NR/SIS
PG16	Designed for paint masking requiring adhesion to many different types of surfaces. PG16 is high temperature resistant to 310° F/155°C, stain resistant and will remove cleanly even when warm.	6.7	8.0	30	25	Solvent NR

		Thickness (mils)	Elongation %	Adhesion (oz/in)	Tensile (lb/in)	Adhesive Type
Weatherak	ple					
PT8	A green coarse crepe backed painter's tape. Removes cleanly up to 8 days after application even when exposed to direct sunlight.	5.6	11.0	22	18	Solvent SIS
PT14	A blue fine-structured crepe backed painter's tape. Provides very clean paint lines and removes cleanly and easily even when exposed to direct sunlight and high humidity levels for up to 14 days. Clearly the "do it yourself" painter's tape of choice.	5.3	11.5	26	23	Solvent SIS
PG20	An aluminized silver crepe backed painter's tape ideal for high temperature exposure and UV exposure. A great body shop and boat yard tape where in-process work may be exposed to UV rays for up to 30 days.	6.8	8.0	33	22	Solvent NR
Colored/S	pecialty					
561	A medium crepe backed masking used for bag sealing, closure or identification. 561 is available in 11 bright colors.	5.2	7.0	46	23	Solvent NR/SIS
PF3	A medium crepe masking often used for temporary harness wrapping, identification, color coding, decorative edging and light weight packaging. Available in 10 colors.	6.2	6.5	33	24	Solvent SIS
543	Designed as check binding tape, also ideal for automatic taping heads due to the balance between strength, adhesion and unwinds. Available in gray, black and white.	5.0	7.0	36	23	Solvent NR
PB1	A moisture resistant black crepe tape ideal for book binding, sealing, or protective covering as the black color provides moderate UV resistance.	5.7	8.0	29	25	Solvent NR
563	A specialty masking tape designed for textile fiber beaming/leasing. Ideal for any application where high adhesion/holding power is required.	6.9	8.0	75	28	Solvent NR
PH7	A low tack specialty paper backed masking used for masking or holding delicate materials in place.	5.9	9.0	18	18	Solvent NR







### Flatback Tape

Intertape® Brand Flatback Tape is designed for a variety of packaging, splicing and tabbing applications. Intertape® Brand Flatback Tape provides a quick, positive seal under a wide range of temperature and humidity conditions.



		Thickness (mils)	Elongation %	Adhesion (oz/in)	Tensile (lb/in)	Adhesive Type
General Gr	ade					
PM308	A dark brown flatback designed for carton sealing. Provides good moisture and tear resistance, yet still hand tearable for easy application.	5.8	3.0	70	34	Solvent- less SIS
530	A solid overall performer, 530's aggressive adhesive yet light weight make it ideal for carton sealing applications providing a cost savings in shipping versus other heavier flatbacks.	7.0	7.0	60	36	Solvent NR/SIS
Medium Gr	rade					
539	A great overall performer, 539 is a low curl, highly conformable flatback designed for carton sealing and splicing. Usable in automatic tape heads.	7.0	7.0	60	36	Solvent NR/SIS
534	The Industry Leader! Ideal for splicing webs or package sealing. Meets U.S. Postal and UPS shipping requirements.	7.0	7.0	50	39	Solvent NR/SIS
PM2	Uniquely colored fatback matches most corrugated cartons for a professionally sealed carton look. A versatile performer.	6.0	4.0	57	37	Solvent NR
Premium G	rade					
538	A bleached flatback backing which resists edge tear yet easily releases from the roll. 538 performs great for a low temperature splicing tape. Meets government specs. CID-A-A-1683B and D5486 type V.	8.4	3.5	93	51	Solvent NR/SIS
PS3	A premium flatback designed for heavy duty packaging/ closure and tabbing. In a natural kraft color, it provides a high quality look when used as a carton sealing tape. Meets government specifications CID A-A 1683B and D5486 Type V.	7.9	4.0	70	51	Solvent NR/SIS
Colored/ID						
546	Ideal for identification and color coding where printability is not required. Available in 5 colors.	7.5	4.0	77	54	Solvent NR/SIS
PF2	A colored flatback that is printable with flexographic inks. PF2 is great for labeling products. Available in 7 colors.	5.8	3.5	31	30	Solvent NR
PF5	Available in the bold colors of florescent red and fluorescent orange. PF5 is a printable flatback ideal for labeling or providing attention-grabbing statements.	6.1	3.0	26	33	Solvent NR
PF14	A printable flatback with high adhesion strength providing great quick stick properties for labeling or tagging many different surfaces, yet the specially designed adhesive platform allows an easier unwind for improved convertability and application. Available in 7 colors.	6.0	3.0	45	32	Solvent SIS
Low Tack/F	Protective					
582	This low tack flatback is machinable and removes cleanly and easily from a variety of surfaces. Whether a finished good or in process material, 582 is great for protecting smooth or polished surfaces.	4.9	3.0	12	17	Solvent NR
SB1	Designed for the manufacturer of stencils, this low tack flatback is machinable and will not gum up drill bits or other equipment.	6.2	3.2	21	28	Solvent NR

#### Need to make a **bold statement?** Want to **stand out** in the crowd?

What better way than to put a little color in your packaging. Intertape® Brand printable colored Flatback Tapes provide you with the ability to do so. Depending upon your application requirements, Intertape Polymer Group™ offers printable flatbacks with natural rubber adhesive platforms on PF2 and PF5 and synthetic rubber adhesive on PF14. To make that really bold statement, check out the fluorescent red and orange PF5. Just another way IPG helps you stand out in the crowd.

#### What do you call the industry standard? We call it 534.

As the industry standard, 534 is the flatback Looking for the best splicing tape? 534 is your tape of choice. With its premium appearance, answer. With an aggressive natural rubber adhesive aggressive adhesive and strong tensile strength, platform, 534 quickly grabs and adheres to most all others try to compare themselves to it, surfaces. Unlike many other brands of splicing but all fall short. tape, 534's strong machine and cross directional strength allow you to splice a web in any direction. If you are looking for the perfect premium Just another reason everyone measures carton-sealing tape, 534 is it. It's a smooth themselves against Intertape® Brand's and shiny backing, provides the 534 Flatback Tape. ultimate in professional appearance. 534 meets UPS and USPS requirements, ensuring your package will arrive sealed and intact.

### Filament/MOPP Tape

Intertape® Brand fiberglass reinforced Filament Tapes deliver superior adhesion for a variety of light to medium load applications. Intertape® Brand MOPP Strapping Tapes are a mono-oriented tensilized polypropylene tape for light duty strapping, palletizing and bundling.



		Thickness (mils)	Elongation %	Adhesion (oz/in)	Tensile (lb/in)	Adhesive Type
Utility Gra	de					
RG-300	A biaxially oriented polypropylene (BOPP) backed filament tape. Ideal for non-critical packaging and shipping. Now available in white or natural.	4.0	3.0	48	100	Solvent- less SIS
788	A (PET) polyester film backed filament tape that offers great scuff/abrasion and moisture resistance. Often used in the food packaging industry. 788 is ideal for carton sealing and unitizing/palleting.	4.9	3.0	36	105	Solvent NR
General G	rade					
RG-303	A biaxially oriented polypropylene (BOPP) backed filament with fiberglass filaments. Designed to meet most packaging, palletizing and utilizing applications. The solventless adhesive quickly grabs most corrugated surfaces. Available in white and natural.	4.2	3.0	49	130	Solvent- less SIS
RG-3	A polyester backed (PET) multi-purpose filament tape with a natural rubber adhesive makes RG3 the industry workhorse!	4.9	3.0	41	131	Solvent NR
Medium G	rade					
RG-315	A biaxially oriented polypropylene (BOPP) backed filament with medium tensile strength, RG315 is ideal for palletizing, unitizing, and strapping where heavier products are being handled.	4.2	4.0	49	175	Solvent- less SIS
RG-15	A polyester backed (PET) medium tensile filament with an aggressive natural rubber adhesive platform. Ideally used for palletizing, unitizing and bundling heavier products.	5.6	4.0	39	175	Solvent NR
RG-12	An excellent alternative to premium grade filaments. RG12 is a polyester (PET) backed filament with rugged performance and an elegant appearance. RG12 is ideal for retail applications.	6.2	4.0	40	275	Solvent NR/SIS
Premium	Grade					
RG-316	For exceptional performance with a thin profile, RG316 is a biaxially oriented polypropylene (BOPP) backed filament with a solventless synthetic rubber adhesive. Designed for medium to heavy duty use. RG316 is ideal for moderate industrial packaging.	6.1	4.0	70	300	Solvent- less SIS
RG-16	The strongest tensile strength filament, this polyester backed (PET) solvent cast, natural rubber tape is ideal for heavy duty industrial applications where strength matters.	8.5	4.5	40	333	Solvent NR
783	A black, high tensile strength, polyester backed (PET) filament tape. Designed for heavy duty industrial applications such as bundling and palletizing. The black PET film offers moderate UV resistance.	8.5	4.5	36	325	Solvent NR

		Thickness (mils)	Elongation %	Adhesion (oz/in)	Tensile (lb/in)	Adhesive Type
Paper-Bac	ked					
750	Easily marked with crayon, pen or rubber stamp, 750 is a medium strength, paper-backed filament with a synthetic rubber pressure-sensitive adhesive.	8.6	5.0	75	200	Solvent- less SIS
RA-2	Easily written on with most crayons, pens or rubber stamps. RA2 is a medium strength, paper-backed filament with an aggressive natural rubber adhesive. Ideal for bundling or tabbing when identification is required.	10.8	4.0	38	198	Solvent NR
RA-1	A fiberglass reinforced, paper-backed filament tape with bi-directional reinforced filaments provides RA-1 a medium impact strength, yet "boardy" enough to make it ideal for automatic applications.	12.4	4.0	53	324	Solvent NR
Specialty						
RN-1	Designed for the sealing of fiber and polyethylene canister tubes, RN1 is a nylon-reinforced, polyester-(PET) backed, filament tape providing an outstanding moisture vapor seal. Removes easily.	5.9	21.0	36	75	Solvent NR
MOPP						
197	Available in clear, white or black, 197 is a mono- oriented, polypropylene (MOPP) tape used for palletizing, unitizing and bundling. 197 is also temperature resistant to 160°F/70°C.	2.7	35.0	55	95	Solvent- less SIS
810	A utility grade, mono-oriented, polypropylene (MOPP) tape ideal for lighter duty palletizing, unitizing and bundling. Available only in black.	3.0	30.0	60	95	Solvent- less SIS



### **Cloth/Duct Tape**

Intertape Polymer Group™ offers a full range of cloth tapes to satisfy even the most demanding applications and industry requirements. From utility grade to nuclear grade, all Intertape® Brand Cloth Tapes are made with high grade raw materials and are held to the highest quality standards.



		Thickness (mils)	Elongation %	Adhesion (oz/in)	Tensile (lb/in)	Adhesive Type
Utility Gra	ade					
AC15	Ideal for retail and non-critical applications. Available in silver and black.	8.0	18.0	54	18	NR
General C	Grade					
AC20	All-purpose home and office use duct tape. Economical and available in 11 colors.	9.0	18.0	54	19	NR
AC30	The maintenance shop duct tape! 10 mils thick. This tape is ideal for maintenance and shop floor applications. From machine repair to leak sealing. Available in silver, black and red.	10.0	18.0	54	20	NR
Medium (	Grade					
AC36	The general contractors duct tape of choice. 11 mils thick with an aggressive natural rubber adhesive platform. Chose AC36 when this high performance counts! Available in silver and black.	11.0	18.0	60	20	NR
AC45	For use in HVAC and abatement applications AC45 hangs and tears straight. Meets UL723, HUD, BOCA and LA county codes. Available in silver, black and red.	12.0	18.0	50	25	NR
AC49	For HVAC applications where UV resistance and a metalized look is preferred. A great choice for use on flexible ducting. Meets UL723, HUD, Boca and LA County Codes.	11.0	18	48	24	NR
Premium	Grade					
AC50	A premium performance HVAC duct tape when a significant level of tensile and tear strength are required. Also provides an excellent moisture barrier. Available in silver, black, white and olive drab.	14.0	14	50	40	NR
AC57	A premiere grade cloth tape listed by Underwriters Laboratories. AC-57 conforms to all code requirements for UL 181B-F. Designed for the professional HVAC contractor. Available in silver and black.	16.0	14	88	MD=40.0 CD=26.6	NR
Nuclear C	Grade					
AC20N	An all-purpose, 9 mil duct tape certified to meet ANSI/ ASME N45.2.2 and NRC Reg. Guide 1.38 para 2C Div. A3.5.2 (1) (A). Enabling it to be used in nuclear power facilities where performance and consistency counts.	9.0	18.0	54	19	NR

### **Double-Coated Tape**

Intertape® Brand Double-Coated Tape features an extremely aggressive tack. Ideal for many industrial uses such as mounting, adhering and bonding applications.



		Thickness (mils)	Elongation %	Adhesion (oz/in)	Tensile (lb/in)	Adhesive Type
Double-Co	ated					
591	The standard for golf grip repair, 591 is also ideal for photograph mounting, carpet installation and textile manufacturing. A heavy duty, double-coated, flatback with a natural rubber adhesive.	12.0 (w/ liner) 7.0 (w/o liner)	3.0	52	34	Solvent NR
592	Made for joining two surfaces, 592 is a double-coated crepe paper tape with an easy-release treated, white paper liner. Ideal for the printing and textile industry, but also used as a splicing tape in certain applications.	10.4 (w/ liner) 6.0 (w/o liner)	4.0	45	23	Solvent NR
593	For UV resistant mounting, 593 is the ideal choice. Great for name plate mounting, assembling outdoor displays, splicing corrugated and paper mounting plastic trim and bonding shrink film window insulation. 593 is a polyester ( PET) film, double-coated tape with an acrylic adhesive.	8.0 (w/ liner) 4.0 (w/o liner)	125	60	16	Solvent Acrylic
597	A double-coated, vinyl (PVC) film with an aggressive natural rubber adhesive, 597 is ideal for mounting porous surfaces together. With a great initial tack, 597 is perfect for sign positioning, mirror manufacturing, engravers, insulating holding on metal buildings contractor and carpet mounting.	9.5 (w/ liner) 5.9 (w/o liner)	30	55	15	Solvent NR

## **Specialty Products**

Intertape® Brand Specialty Products are designed for unique applications that require a specific product or product characteristic.



		Thickness (mils)	Elongation %	Adhesion (oz/in)	Tensile (lb/in)	Adhesive Type
Vinyl Electr	ical					
619	Premium grade electrical tape, PVC, black vinyl, all-weather, flame retardant, great dielectric strength, UL Listed.	8.0	200	16	20	Solvent NR
6180	General purpose electrical tape, black vinyl, electrical insulating, good dielectric strength, UL Listed.	7.0	200	16	18	Solvent NR
8120	Transfer adhesive, self-wound, unsupported, acrylic adhesive.	5.0/2.0	_	64	-	Acrylic
Flagging/B	arricade					
6880	Flagging ribbon, narrow width, bright, day-glo colors.	_	_	_	_	_
6890	Barricade ribbon, bright yellow with black lettering (stock prints only).	-	_	_	-	_
Spray Adhesive						
AC50SP	Web spray adhesive, 24 fl. oz., 17 net oz.	_	-	-	-	-

#### **IPG Corporate Profile**

Intertape Polymer Group Inc. (IPG) is an acknowledged leader in the packaging industry. Leveraging its advanced manufacturing technologies, extensive research and development capabilities and a comprehensive strategic acquisition program, the company has assembled the broadest and deepest range of products in the industry. This strategy allows IPG to create a sustainable economic advantage for its customers through its commitment to deliver a portfolio of solutions around the most efficient supply chain in the industry.

IPG manufactures a broad range of packaging products and systems that reflect the needs of both its industrial and retail customers. These include one of the largest offerings of tape available: pressure-sensitive and wateractivated, carton-sealing, masking, filament, flatback, cloth/duct, double-coated, high performance specialty, electrical, automotive, and HVAC tapes. Additional products include shrink film and stretch film as well as carton-sealing equipment, ink jet printing systems and labeling systems.

Intertape is a leader in the engineered coated products and flexible intermediate bulk container (FIBC) industries. With heavy emphasis placed on R&D, IPG is bringing to market many innovative new products for the agricultural and structural fabrics industries.

Established in 1981 with headquarters in Montreal, Quebec and Bradenton, Florida, Intertape employs approximately 2,600 employees with operations in 16 locations, including 12 manufacturing facilities in North America and Europe.

Intertape Polymer Group Inc. is a publicly traded company with its common shares listed on the New York Stock Exchange (NYSE) and the Toronto Stock Exchange (TSE) under the stock symbol "ITP."



#### **Customer Service**

Toll Free: 800-IPG-8273/800-474-8273

 Marysville, MI Fax:
 810-364-9164

 Columbia, SC Fax:
 800-462-1293

 Montreal, QC Fax:
 800-561-3671

Technical Help Desk: 877-4IPG-TEC/877-447-4832 www.intertapepolymer.com • E-mail: Info@itape.com

